

# TECHNOFLEX PVC GREEN SUCTION HOSE



**Color:** Green With Cream Helix.

**Temperature range:** - 10°C + 60°C / + 14°F + 140°F.

**Features:** PVC hose reinforced with an ANTI- SHOCK RIGID PVC spiral. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, abrasion, atmospheric agents and most chemicals.

**Applications:** Excellent for suction in general, particularly suitable to be used on slurry machines.

## TECHNICAL DATA

PART NUMBER	INSIDE Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Working Pressure	Burst Pressure	Vacuum	Bending Radius	Roll Length	Volume
	mm	mm	mm	g/m	Bar	Bar	m H2O	mm	m	m³
01 020. 0 000	20	3,1	3,5	300	7	21	10	100	50	0,070
01 025. 0 000	25	3,3	3,7	390	6	18	10	125	50	0,094
01 032. 0 000	31,8	3,9	4,3	580	6	18	10	160	50	0,142
01 038. 0 000	38,1	3,8	4,4	670	5	15	10	190	50	0,190
01 050. 0 000	50	4,2	4,8	960	4	12	10	250	50	0,310
01 052. 0 000	50,8	4,2	4,8	970	4	12	10	250	50	0,314
01 063. 0 000	63,5	4,7	5,3	1350	4	12	9	315	50	0,501
01 076. 0 000	76,2	4,9	5,6	1630	3	9	9	380	50	0,646
01 080. 0 000	80	5,0	5,9	1770	3	9	9	400	50	0,720
01 100. 0 000	100	5,9	6,9	2590	3	9	8,5	500	30	0,768
01 102. 0 000	102	5,9	6,9	2640	3	9	8,5	500	30	0,782
01 127. 0 000	127	6,2	7,3	3450	2,5	7,5	8	630	30	1,228
01 150. 0 000	151,5	6,7	7,9	4420	2	6	7	750	20	1,312
01 152. 0 000	152,4	6,7	7,9	4410	2	6	7	750	20	1,319

**Authorized Distributor:**  
MOHAMMED AHMED AL-AWANI TRADING COMPANY

Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service